

# UP S LUB 20

## Anti-friction agents and lubricants

UP S LUB 20 is a special lubricant for fiber optical installation for min and micro cable with blowing machine. It's a water emulsion of different kind of polymers.

UP S LUB 20 is a water base product with high efficiency of lubricant. It's reduce dramatically the friction. S LUB is white liquid little bit viscosity.

UP S LUB 20 adhere perfectly at the cable surface or at the internal surface of the pipe. It's leave a very tiny film of lubricant and does not make the glue effect.

Product Use: Cable and Duct Pre-lubrication

### Suggested Uses quantities for 1000m

internal duct diam $\varnothing$ mm	Quantities of product (ml)
20 – 30	600
30 – 40	700
40 – 50	1000

The real quantities can be change due to a condition of the pipe or how is difficult the pipe long.

**Use:**

Shake the bottle before use, then put the product inside in the pipe. Then pre-lubricant the pipe with a little piece of sponge.

The product is also suitable for blowing machine with oil dispenser to lubricating the fiber during the pushing.

The UP S LUB 20, also can be useful to lubricate the fiber optic before or after blowing machine. It's depend on the appliance with iron wheel or with rubber wheel.

Technical Specification:	White liquid tiny viscosity
Odor:	None
Viscosity:	120 sec. Ford cup diam. mm 4 at 20C°
Specific gravity:	1,030 +- 0,03 gr/cm <sup>3</sup>
pH:	7,5 +- 0,5
Inflammability:	Noninflammable
Temperature:	-5° + 70° C.
Biodegradability:	The product is biodegradable
Toxic:	The product is not toxic

**Packaging:**

Product Code	Wrapping / Packaging
VSLUB100XL05-12	bottle 500 gr / box 12 pc
VSLUB100XL1-15	bottle 1 kg / box 15 pc
VSLUB100XL1-12	bottle 1 kg / box 12 pc
VSLUB100XL1-06	bottle 1 kg / box 6 pc
VSLUB100XL5	tank 5 kg / 1 pc
VSLUB100XL10	tank 10 kg / 1 pc
VSLUB100XL20	tank 20 kg / 1 pc
VSLUB100XL25	tank 25 kg / 1 pc

